

# s25 sCharge PoE

factsheet

Cable length 33 cm.  
Lightning cable also with 3 m length available.



Lightning



micro USB



USB-C



Product name	<b>sCharge</b> PoE 1040 Lightning	<b>sCharge</b> PoE 1040 micro USB	<b>sCharge</b> PoE 1040 USB-C
Short name	<b>s25 L</b>	<b>s25 m</b>	<b>s25 C</b>
EAN code	4260258610253	4260258612257	4260258612035
Manuf. part no.	sCh-PoE1040-8pin	sCh-PoE1040-mUSB	sCh-PoE1040-USB-C
Description	Passive PoE Splitter WS-PoE-5V-2Amps plus adapter cable to Apple Lightning connector or micro USB. Together with a 24 volts power supply and a single port PoE injector it is an easy power solution for a distance up to 100m (328 ft) Perfect for conference rooms, kiosks and anywhere else you need a digital display. Stream data with an Apple Ethernet to Lightning adapter for wired data.		
Compatible	s25 L s25 m s25 C	all sDock Fix, all sDocks (2nd generation) Androids, ... all sDocks for iPads with USB-C or other wall mounts	
Technical Data	Input voltage Output voltage Operating Humidity Operating Temperature Cable connector length	24 V (10 - 40V) 5 V 5% to 90% -10 - 60C 330mm, 13 inches. Lightning Cable with 3m length is available. Ideal for glass wall mounting.	
Approval	CE, FCC (EMV, FCC part 15 subpart b)		
Dimensions	Splitter: 50 x 33 x 20 mm		
Customs tariff no.	85044090		
Country of origin	China		